



Features

- . Wide input 90V to 264VAC, 50~60Hz suitable for worldwide
- . Output voltage selectable from 14.6V to 58.8Vdc
- . Class B Conducted and Radiated EMI for information devices
- . 2 stage charging characteristic with 2 color LED indicator
- . Metal case and fan forced convection better for cooling
- . High Efficiency up to 90% and power factor up to 0.98
- . Over Temperature/ Reverse Connection/ Short Circuit Protections

Safety Standards

- . IEC60335-1:2010+A1:2013 + A2:2016 /IEC60335-2-29 CB
- . UL1310:2018 Ed.7+R:09 + CSA C22.2#223:2015 Ed.3
- . EN 60335-2-29 /EN60335-1:2012 for European Union
- . AS/NZS 60335.2.29: 2017 for Australia and New Zealand
- . J61558-1/J61558-2-16 /J3000 /J55014-1 for Japan market.



Product Description:

It is a highly reliable 240W desktop style battery charger solution with wide range 90-264Vac input and single output available from 14.6V to 58.8Vdc for different voltage batteries. Equipped with a standard IEC320-C14 AC inlet. The entire series supplies different models which is suitable for 12V /24V /36V /48V lead-acid batteries and Li-ion batteries. This 240W series battery charger is widely used in charging electric bicycles, tricycles, scooters, power tools and other electric-related equipment.

With the efficiency up to 90% and built-in active PFC with PF>0.98, this 240W battery charger is designed according to worldwide satisfy standards. The charger utilizes aluminum alloy case and smart chip controlled fan for cooling keeping the charger in low temperature rise.

Technical Specification

Typ. Model	AP-PF240CH01460140	AP-PF240CH02920080	AP-PF240CH02940080	AP-PF240CH04380060	AP-PF240CH05880040
Output					
Output Voltage	14.6VDC	29.2VDC	29.4VDC	43.8VDC	58.8VDC
Charging Current	14A	8A	8A	6A	4A
Output Power	204.4W Max.	233.6W Max.	235.2W Max.	262.8W Max.	235.2W Max.
Voltage Accuracy	±0.2V	±0.2V	±0.2V	±0.2V	±0.2V
Ripple & Noise	200mVp-p	200mVp-p	250mVp-p	300mVp-p	400mVp-p
Standby Power	≤0.21W	≤0.21W	≤0.21W	≤0.21W	≤0.21W
Input					
Input voltage	90 - 264Vac or 127- 374Vdc				
Input Frequency	50-60Hz (When the input is AC)				
Input Current	3A Max. @ 100 ~240Vac 50/60Hz input				
Inrush Current	100A Max. @ 100 ~240Vac 50/60Hz input				
Power Factor	>0.98 @ 120Vac 60Hz input; >0.95 @230Vac 50Hz input				
Efficiency (Typ.)	89%	90%	90%	90%	90%
Leakage Current	≤3.5mA @ full input range				
Protections					
Over temperature	Shut down o/p voltage, re-power on to recover				
Short Circuit	When Short Circuit happened ,charger will turn off. No damage.				
Reverse Connection	When the battery is polarity reversed ,the charger will cut off the connection between the circuit and the battery				
Environmental					
Operation Temperature	-10°C to +40°C, 10%RH to 90%RH				
Operation Altitude	≤2000m @ full load and rated operating temperatures				
MTBF	≥50000Hrs @ full load and rated operating temperatures				
Mechanical					
Dimensions (W x L x H)	204.0 x 88.0 x 48.0mm (8.03 x 3.46 x 1.89 inch)				
Unit Weight	800g±25 grams				
Packing Information	10pcs/ Carton, carton dimensions:47*37*20cm, 9.0kgs/ Carton				

TEST REPORT

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITDION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-0.2V ~ +0.2V	I/P:90VAC~264VAC O/P:FULL~MIN. LOAD / Ta:25°C	-0.09V ~ +0.12V	P
2	CONTINUOS OUTPUT CURRENT	14A	I/P:230VAC /I/P:115VAC O/P:CV=12V / Ta:25°C	14.01A /230VAC 13.99A/115VAC	P
3	LED INDICATOR	Charging (CC): BLUE Floating charging: GREEN	I/P:230VAC O/P: SETTING / Ta:25°C	>0.810A, LED: BLUE <0.725A, LED: GREEN	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITDION	RESULT	VERDICT
1	VOLTAGE RANGE	90VAC~264VAC	I/P:TESTING O/P:FULL LOAD / Ta:25°C	83V~264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 100VAC ~ 240VAC O/P:FULL~MIN LOAD / Ta:25°C	TEST: OK	P
3	POWER FACTOR	0.96 / 230VAC 0.98 / 115VAC	I/P:230VAC IP: 115VAC O/P: FULL LOAD & Ta:25°C	PF=0.973 / 230VAC PF=0.982 / 115VAC	P
4	EFFICIENCY	90% (Typ)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	90.8%	P
5	AVERAGE EFFICIENCY	>89% (LEVEL VI)	I/P:115/230VAC & O/P:25%、50%、75%、 100% LOAD & Ta:25°C	89.89% (115VAC) 89.83% (230VAC)	P
6	AC CURRENT	3.0A (Max)	I/P:100VAC & O/P:FULL LOAD Ta:25°C	2.72A	P
7	INRUSH CURRENT	<80A COLD START	I/P: 230VAC / O/P:FULL LOAD Ta:25°C	57.58A	P
8	LEAKAGE CURRENT	<3.5mA	I/P:240VAC & O/P:Min LOAD Ta:25°C	L-FG:1.59mA N-FG:1.58mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITDION	RESULT	VERDICT
1	OVER LOAD PROTECTION	95 ~ 115%	I/P:230VAC I/P:115VAC O/P:TESTING Ta:25°C	100.6% /230VAC 100.6% /115VAC Constant current limiting recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	15.0V ~ 16.5	I/P:230VAC /I/P:115VAC O/P:MIN LOAD Ta:25°C	15.33V /230VAC 15.28V /115VAC Shut down o/p voltage, re-power on to recover	P
3	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD & Ta:25°C	NO DAMAGE HICCUP MODE	P
4	REVERSE CONNECTION	REVERSE CONNECTION for 1H NO DAMAGE	I/P: 230VAC O/P: TESTING Ta:25°C	Shut down O/P voltage, no damage. Re-power on to recover	P

SAFETY TEST & E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITDION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 1.5KVAC/min I/P- FG: 1.5KVAC/min O/P-FG:0.5KVAC/min	I/P-O/P: 1.6 KVAC/min I/P-FG: 1.6 KVAC/min O/P-FG:0.6 KVAC/min Ta:25°C	I/P-O/P:2.929mA I/P-FG: 3.625mA O/P-FG:0.895mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>10MΩ I/P-FG: 500VDC>10MΩ O/P-FG:500VDC>10MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 9999MΩ I/P-FG: 9999MΩ O/P-FG:9999 MΩ NO DAMAGE	P
3	CONDUCTION	BS EN/EN55014(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL/50% LOAD Ta: 25°C	PASS Test by certified Lab	P
4	RADIATION	BS EN/EN55014(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
5	SURGE	BS EN/EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P
6	E.S.D	BS EN/EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	LINDA	JUDY	ZHANG DL