



Features

- . Input 90V to 264VAC, 50~60Hz suitable for worldwide use
- . Output voltage optional from 12V to 52Vdc constant voltage
- . Protections: Short Circuit / Overload / Over Voltage Protection
- . 100% full load burn-in test for 2Hrs to make every unit reliable
- . Small and compact size, built-in active PFC function
- . Cooling by free air convection, operating temperature -20~50°C
- . Long life and high reliability design with 2 years warranty

Safety Standards

- . IEC62368-1 CB report for worldwide use
- . UL62368-1 + CAN/CSA 62368-1 for USA and Canada
- . EN 62368-1:2014/A11:2017 for European Union
- . AS/NZS 62368.1:2018 for Australia and New Zealand
- . J62368-1 for Japan and GB4943.1 for China market.



Product Description:

It is a highly reliable and quality 120W open frame switching power supply solution with wide range 90-264Vac input and designed strictly according to the international safety standards. It's built-in PFC function with PF>0.95. The entire series supplies different models with output voltages ranging between 12Vdc and 52Vdc that can satisfy the demands for various types of consumer electronic devices, household electronic device, communication device and so on. The 120W open frame type switching power supply solution is built-in full protections of over load / short circuit and over voltage with small and compact size of 101.6 x 50.8 x 29mm. The entire series can operate at the ambient temperature between -20 and 50°C without any derating under air convection.

Technical Specification

Typ. Model	KEP1121-12	KEP1121-24	KEP1121-27	KEP1121-36	KEP1121-48
Output					
Output Voltage	12VDC	24VDC	24VDC	36VDC	48VDC
Rated Current	10A	5A	4.44A	3.33A	2.5A
Current Range	0 ~ 10A	0 ~ 5A	0 ~ 4.44A	0 ~ 3.33A	0 ~ 2.5A
Output Power	120W Max.	120W Max.	120W Max.	120W Max.	120W Max.
Voltage Tolerance	±3%	±3%	±2%	±2%	±2%
Ripple & Noise	250mVp-p	250mVp-p	300mVp-p	300mVp-p	350mVp-p
Input					
Input voltage	90 - 264Vac or 120- 370Vdc				
Input Frequency	50-60Hz (When the input is AC)				
Input Current	2.0A Max. @ 100 ~240Vac 50/60Hz input				
Inrush Current	120A Max. @ 100 ~240Vac 50/60Hz input				
Efficiency (Typ.)	85%	88%	88%	89%	89%
Leakage Current	≤ 1mA @ full input range				
Protections					
Over current	115~150% rated output power. Auto-Recovery when the fault is removed				
Short Circuit	No damage. Auto-Recovery when the fault is removed				
Over temperature	Shut down o/p voltage, re-power on to recover				
Environmental					
Operation Temperature	-20°C to +50°C, 20%RH to 90%RH				
Storage Temp, Humidity	-45~ +85°C, 10%RH to 95%RH				
Operation Altitude	≤3000m @ full load and rated operating temperatures				
MTBF	≥50000Hrs @ full load and rated operating temperatures				
Mechanical					
Dimensions (L x W x H)	101.6 x 50.8 x 29.0mm (4.00 x 2.00 x 1.14 inch)				
Unit Weight	250g±20 grams				
Packing Information	48pcs/ Carton, carton dimensions:47*37*20cm, 13kgs/ Carton				

TEST REPORT

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	RIPPLE & NOISE	250mVp-p (Max)	I/P:230VAC / O/P:FULL LOAD / Ta:25°C	139mVp-p	P
2	VOLTAGE TOLERANCE	-3% ~ +3% (Max)	I/P:90VAC~264VAC O/P:FULL~MIN. LOAD / Ta:25°C	-1.3% ~ +1.3% of output voltage	P
3	LINE REGULATION	-1% ~ +1% (Max)	I/P:90VAC ~264VAC O/P:FULL LOAD / Ta:25°C	-0.06% ~ +0.06% of output voltage	P
4	LOAD REGULATION	-1% ~ +1% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD / Ta:25°C	-0.63% ~ +0.63% of output voltage	P
5	OVER/UNDERSHOOT	<±5%	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	1.2%	P
6	SET UP TIME	3000 mS (Max)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	1550 mS	P
7	RISE TIME	50 mS (Max)	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	29 mS	P
8	HOLD UP TIME	8 mS (Min)	I/P: 115VAC O/P:FULL LOAD / Ta:25°C	12 mS	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	VOLTAGE RANGE	90VAC~264VAC	I/P:TESTING O/P:FULL LOAD / Ta:25°C	82V~264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 100VAC ~ 240VAC O/P:FULL~MIN LOAD / Ta:25°C	TEST: OK	P
3	EFFICIENCY	85% (Typ)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	86.32%	P
4	AVERAGE EFFICIENCY	>83%	I/P:115/230VAC & O/P:25%、50%、75%、100% LOAD & Ta:25°C	83.66% (115VAC) 83.96% (230VAC)	P
5	AC CURRENT	2.0A (Max)	I/P:100VAC & O/P:FULL LOAD Ta:25°C	1.36A	P
6	INRUSH CURRENT	<120A COLD START	I/P: 230VAC / O/P:FULL LOAD Ta:25°C	58.85A	P
7	LEAKAGE CURRENT	< 2.5mA	I/P:240VAC & O/P:Min LOAD Ta:25°C	L-FG:1.17mA N-FG:1.13mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	OVER LOAD PROTECTION	115 ~ 165% (Typ)	I/P:230VAC & O/P:TESTING Ta:25°C	146.5% HICCUP MODE	P
2	OVER VOLTAGE PROTECTION	115 ~ 135% (Typ)	I/P:230VAC O/P:MIN LOAD & Ta:25°C	Hiccup mode ,recovers automatically after fault condition is removed	P
3	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD & Ta:25°C	NO DAMAGE HICCUP MODE	P

SAFETY TEST & E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3KVAC/min I/P- FG: 2KVAC/min O/P-FG:0.5KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 2.4KVAC/min O/P-FG: 0.6KVAC/min Ta:25°C	I/P-O/P:4.80mA I/P-FG: NA O/P-FG: NA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 9999MΩ I/P-FG: NA O/P-FG: NA NO DAMAGE	P
3	CONDUCTION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL/50% LOAD Ta: 25°C	PASS Test by certified Lab	P
4	RADIATION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
5	SURGE	BS EN/EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P
6	E.S.D	BS EN/EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	ZHU LI	WANG LW	ZHANG DL