



**Features**

- . Input 90V to 264VAC, 50~60Hz suitable for worldwide use
- . Output voltage optional from 12V/54V and 24V/54V
- . Protections: Short Circuit / Overload / Over Voltage Protection
- . 100% full load burn-in test for 2Hrs to make every unit reliable.
- . Built-in PFC function and PF> 0.94, ow leakage current<0.5mA
- . Cooling by free air convection, operating temperature -20~50°C
- . Long life and high reliability design with 2 years warranty

**Safety Standards**

- . IEC62368-1 CB report for worldwide use
- . UL62368-1 + CAN/CSA 62368-1 for USA and Canada
- . EN 62368-1:2014/A11:2017 for European Union
- . AS/NZS 62368.1:2018 for Australia and New Zealand
- . J62368-1 for Japan and GB4943.1 for China market.



**Product Description:**

It is a highly reliable dual output 170W open frame network equipment power supply solution with wide range 90-264Vac input and designed strictly according to the international safety standards. The entire series supplies two models with output voltages 12V/54V and 24V/54V. The product is suitable for various types of network equipment, consumer electronic devices, household electronic device, communication device and so on. The 170W dual output switching power supply solution is built-in full protections of over load / short circuit and over voltage. The design is in low leakage current <0.5mA and with fixed working switching frequency at 65KHz.

**Technical Specification**

Typ. Model	KNW170A01		KNW170A02	
<b>Output</b>				
Output Number	CH1	CH2	CH1	CH2
Output Voltage	12VDC	54VDC	24VDC	54VDC
Rated Current	3.5A	2.4A	2A	2.25A
Current Range	0.4 ~ 3.5A	0.2 ~ 2.4A	0.2 ~ 2.0A	0.2 ~ 2.25A
Output Power	170W Max.		170W Max.	
Voltage Tolerance	±4%	±5%	±4%	±5%
Ripple & Noise	200mVp-p	350mVp-p	200mVp-p	350mVp-p
<b>Input</b>				
Input voltage	90 - 264Vac or 120- 370Vdc			
Input Frequency	50-60Hz (When the input is AC)			
Input Current	3.0A Max. @ 100 ~240Vac 50/60Hz input			
Inrush Current	60A Max. @ 100 ~240Vac 50/60Hz input			
Efficiency (Typ.)	83%		83%	
Leakage Current	≤0.5mA @ full input range			
<b>Protections</b>				
Over current	180~230W. Auto-Recovery when the fault is removed			
Short Circuit	No damage. Auto-Recovery when the fault is removed			
Over temperature	Shut down o/p voltage, re-power on to recover			
<b>Environmental</b>				
Operation Temperature	-20°C to +50°C, 20%RH to 90%RH			
Storage Temp, Humidity	-45~ +85°C, 10%RH to 95%RH			
Operation Altitude	≤3000m @ full load and rated operating temperatures			
MTBF	≥50000Hrs @ full load and rated operating temperatures			
<b>Mechanical</b>				
Dimensions (L x W x H)	254.0 x 88.5 x 33.0mm (10.00 x 3.48 x 1.30 inch)			
Unit Weight	480g±15 grams			
Packing Information	25pcs/ Carton, carton dimensions:47*37*20cm, 13.5kgs/ Carton			

**TEST REPORT**
**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	RIPPLE & NOISE	CH1:200mVp-p (Max) CH2:350mVp-p (Max)	I/P:230VAC / O/P:FULL LOAD / Ta:25°C	155mVp-p 223mVp-p	P
2	VOLTAGE TOLERANCE	CH1: -4% ~ +4% CH2:-5% ~ +5%	I/P:90VAC~264VAC O/P:FULL~MIN. LOAD / Ta:25°C	CH1: -0.88% ~+2.58% CH2: -1.36% ~+4.18%	P
3	LINE REGULATION	-2% ~ +2% (Max)	I/P:90VAC ~264VAC O/P:FULL LOAD / Ta:25°C	-0.6% ~ +0.8% of output voltage	P
4	LOAD REGULATION	-4% ~ +4% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD / Ta:25°C	-0.95% ~ +2.36% of output voltage	P
5	OVER/UNDERSHOOT	<±5%	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	1.0%	P
6	SET UP TIME	3000 mS (Max)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	1880 mS	P
7	RISE TIME	30 mS (Max)	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	26 mS	P
8	HOLD UP TIME	10 mS (Min)	I/P: 115VAC O/P:FULL LOAD / Ta:25°C	17 mS	P

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	VOLTAGE RANGE	90VAC~264VAC	I/P:TESTING O/P:FULL LOAD / Ta:25°C	85V~264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 100VAC ~ 240VAC O/P:FULL~MIN LOAD / Ta:25°C	TEST: OK	P
3	EFFICIENCY	83% (Typ)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	83.96%	P
4	AVERAGE EFFICIENCY	>81%	I/P:115/230VAC & O/P:25%、50%、75%、 100% LOAD & Ta:25°C	81.88% (115VAC) 82.37% (230VAC)	P
5	AC CURRENT	3.0A (Max)	I/P:100VAC & O/P:FULL LOAD Ta:25°C	2.21A	P
6	INRUSH CURRENT	<60A COLD START	I/P: 230VAC / O/P:FULL LOAD Ta:25°C	41.3A	P
7	LEAKAGE CURRENT	< 0.5mA	I/P:240VAC & O/P:Min LOAD Ta:25°C	L-FG:0.39mA N-FG:0.39mA	P

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	OVER LOAD PROTECTION	180 ~ 230W (Typ)	I/P:230VAC & O/P:TESTING Ta:25°C	206.4W HICCUP MODE	P
2	OVER VOLTAGE PROTECTION	115 ~ 135% (Typ)	I/P:230VAC O/P:MIN LOAD & Ta:25°C	Hiccup mode ,recovers automatically after fault condition is removed	P
3	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD & Ta:25°C	NO DAMAGE HICCUP MODE	P

**SAFETY TEST & E.M.C TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3KVAC/min I/P- FG: 2KVAC/min O/P-FG:0.5KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 2.4KVAC/min O/P-FG: 0.6KVAC/min Ta:25°C	I/P-O/P:5.16mA I/P-FG: 5.09mA O/P-FG: 3.21mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 9999MΩ I/P-FG: 9999MΩ O/P-FG:9999 MΩ NO DAMAGE	P
3	CONDUCTION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL/50% LOAD Ta: 25°C	PASS Test by certified Lab	P
4	RADIATION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
5	SURGE	BS EN/EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P
6	E.S.D	BS EN/EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	ZHU LI	WANG LW	ZHANG DL