



Features

- . Input voltage 176 ~ 264VAC 50/60Hz or 200~360VDC
- . Output voltage select able from 3.3V to 24Vdc constant voltage
- . Protections: Short Circuit / Overload / Over Voltage Protection
- . High efficiency, long life and high reliability with small size
- . All using high quality 105°C long life electrolytic capacitors
- . Low cost solution and LED indicator for power on
- . Efficiency is no less than 75% and 2 years guarantee.

Safety Standards

- . IEC62368-1 CB report for worldwide use
- . UL62368-1 + CAN/CSA 62368-1 for USA and Canada
- . EN 62368-1:2014/A11:2017 for European Union
- . AS/NZS 62368.1:2018 for Australia and New Zealand
- . J62368-1 for Japan and GB4943.1 for China market.



Product Description:

It is a low cost and reliable 12VDC 1.3A 15W single output switching power supply solution with 176-264Vac or 200 - 360Vdc input and designed strictly according to the international safety standards. The output voltage is adjustable by the potentiometer by +/-10% of output voltage. This 12Vdc 1.3A switch mode power supply is suitable for various types of industrial automation machinery, industrial control system, mechanical and electrical equipment, electronic instruments and so on. This switching power supply utilizes aluminum alloy housing with cellular shape cover which is better for free air convection cooling with dimensions of 110.5 * 46* 31mm .

Technical Specification

Typ. Model	TL-15S-3.3	TL-15S-5	TL-15S-9	TL-15S-12	TL-15S-24
Output					
Output Voltage	3.3VDC	5VDC	9VDC	12VDC	24VDC
Rated Current	3A Max.	3A Max.	1.7A Max.	1.3A Max.	0.7A Max.
Current Range	0 ~ 3A	0 ~ 3A	0 ~ 1.7A	0 ~ 1.3A	0 ~ 0.7A
Output Power	9.9W Max.	15W Max.	15W Max.	15W Max.	15W Max.
Voltage Tolerance	±5%	±5%	±5%	±5%	±5%
Ripple & Noise	80mVp-p	80mVp-p	100mVp-p	100mVp-p	150mVp-p
Input					
Input voltage	176 - 264Vac or 200- 360Vdc				
Input Frequency	50-60Hz (When the input is AC)				
Input Current	0.3A Max. @ 100 ~240Vac 50/60Hz input				
Inrush Current	40A Max. @ 100 ~240Vac 50/60Hz input				
Efficiency (Typ.)	65%	71%	73%	75%	80%
Leakage Current	≤0.5mA @ full input range				
Protections					
Over current	110~130% rated output power. Auto-Recovery when the fault is removed				
Short Circuit	No damage. Auto-Recovery when the fault is removed				
Over temperature	Shut down o/p voltage, re-power on to recover				
Environmental					
Operation Temperature	0°C to +45°C, 20%RH to 90%RH				
Storage Temp, Humidity	-45~ +85°C, 10%RH to 95%RH				
Operation Altitude	≤2000m @ full load and rated operating temperatures				
MTBF	≥50000Hrs @ full load and rated operating temperatures				
Mechanical					
Dimensions (W x L x H)	110.5 x 46.0 x 31.0mm (4.35 x 1.81 x 1.18 inch)				
Unit Weight	130g±10 grams				
Packing Information	60pcs/ Carton, carton dimensions:47*37*20cm, 9.5kgs/ Carton				

TEST REPORT

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	RIPPLE & NOISE	100mVp-p (Max)	I/P:230VAC / O/P:FULL LOAD / Ta:25°C	66mVp-p	P
2	VOLTAGE TOLERANCE	-5% ~ +5% (Max)	I/P:176VAC~264VAC O/P:FULL~MIN. LOAD / Ta:25°C	-2% ~ +2% of output voltage	P
3	LINE REGULATION	-1% ~ +1% (Max)	I/P:176VAC ~264VAC O/P:FULL LOAD / Ta:25°C	-0.05% ~ +0.05% of output voltage	P
4	LOAD REGULATION	-3% ~ +3% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD / Ta:25°C	-0.92% ~ +0.92% of output voltage	P
5	OVER/UNDERSHOOT	<±5%	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	0.8%	P
6	SET UP TIME	2000 mS (Max)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	1220 mS	P
7	RISE TIME	30 mS (Max)	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	25 mS	P
8	HOLD UP TIME	10 mS (Min)	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	14 mS	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	VOLTAGE RANGE	176VAC~264VAC	I/P:TESTING O/P:FULL LOAD / Ta:25°C	158V~264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 176VAC ~ 240VAC O/P:FULL~MIN LOAD / Ta:25°C	TEST: OK	P
3	EFFICIENCY	75% (Typ)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	75.60%	P
4	AVERAGE EFFICIENCY	>73%	I/P:230VAC & O/P:25%、50%、75%、100% LOAD & Ta:25°C	73.44% (230VAC)	P
5	AC CURRENT	0.3A (Max)	I/P:230VAC & O/P:FULL LOAD Ta:25°C	0.19A	P
6	INRUSH CURRENT	<40A COLD START	I/P: 230VAC / O/P:FULL LOAD Ta:25°C	26.08A	P
7	LEAKAGE CURRENT	< 0.5mA	I/P:230VAC & O/P:Min LOAD Ta:25°C	L-FG:0.38mA N-FG:0.38mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110 ~ 130% (Typ)	I/P:230VAC & O/P:TESTING Ta:25°C	120.8% HICCUP MODE	P
2	OVER VOLTAGE PROTECTION	115 ~ 135% (Typ)	I/P:230VAC O/P:MIN LOAD & Ta:25°C	Hiccup mode ,recovers automatically after fault condition is removed	P
3	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD & Ta:25°C	NO DAMAGE HICCUP MODE	P

SAFETY TEST & E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3KVAC/min I/P- FG: 2KVAC/min O/P-FG:0.5KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 2.4 KVAC/min O/P-FG:0.6 KVAC/min Ta:25°C	I/P-O/P:3.82mA I/P-FG: NA O/P-FG:NA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 9999MΩ I/P-FG: 9999MΩ O/P-FG:9999 MΩ NO DAMAGE	P
3	CONDUCTION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL/50% LOAD Ta: 25°C	PASS Test by certified Lab	P
4	RADIATION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
5	SURGE	BS EN/EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P
6	E.S.D	BS EN/EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	ZHU LI	WANG LW	ZHANG DL