



**Features**

- . Wide input 90V to 264VAC, 50~60Hz suitable for worldwide
- . Output voltage selectable from 12V to 56Vdc constant voltage
- . Class B Conducted and Radiated EMI for information devices
- . Meet ErP & DoE efficiency level VI requirements
- . No load power consumption < 0.21 W; height of 30mm
- . High Efficiency up to 92% and power factor up to 0.98
- . Over-Voltage/Load/Temperature & Short Circuit protections

**Safety Standards**

- . IEC62368-1 CB report for worldwide use
- . UL62368-1 + CAN/CSA 62368-1 for USA and Canada
- . EN 62368-1:2014/A11:2017 for European Union
- . AS/NZS 62368.1:2018 for Australia and New Zealand
- . J62368-1 for Japan and K60950-1 for Korea market.



**Product Description:**

It is a highly reliable 250W Ultra-thin desktop style switching power adapter solution with wide range 90-264Vac input and designed strictly according to the international safety standards. Equipped with a standard IEC320-C6/C8/C14 AC inlet. The entire series supplies different models with output voltages ranging between 12Vdc and 56Vdc that can satisfy the demands for various types of consumer electronic devices, office facilities, industrial equipment and so on.

With the efficiency up to 92% and no load consumption power <0.21W, this 200W power adapter is built-in active PFC with PF>0.98. The entire series utilizes the 94V-0 flame retardant plastic housing and the temperature resistance is up to 120 degrees.

**Technical Specification**

Typ. Model	KA1252120J	KA1252240K	KA1252320L	KA1252420L	KA1252560M
<b>Output</b>					
Output Voltage	12VDC	24VDC	32VDC	42VDC	56VDC
Output Current	17.50A Max.	10.41A Max.	7.81A Max.	5.95A Max.	4.46A Max.
Output Power	220W Max.	250W Max.	250W Max.	250W Max.	250W Max.
Voltage Tolerance	±5%	±5%	±5%	±5%	±5%
Ripple & Noise	300mVp-p	350mVp-p	400mVp-p	400mVp-p	500mVp-p
Standby Power	≤0.21W	≤0.21W	≤0.21W	≤0.21W	≤0.21W
<b>Input</b>					
Input voltage	90 - 264Vac or 127- 374Vdc				
Input Frequency	50-60Hz (When the input is AC)				
Input Current	3.5A Max. @ 100 ~240Vac 50/60Hz input				
Inrush Current	140A Max. @ 100 ~240Vac 50/60Hz input				
Power Factor	>0.98 @ 120Vac 60Hz input; >0.95 @230Vac 50Hz input				
Efficiency (Typ.)	91%	91%	92%	92%	92%
Leakage Current	≤0.25mA @ full input range				
<b>Protections</b>					
Over current	110~150% rated output power. Auto-Recovery when the fault is removed				
Short Circuit	No damage. Auto-Recovery when the fault is removed				
Over temperature	Shut down o/p voltage, re-power on to recover				
<b>Environmental</b>					
Operation Temperature	0°C to +40°C, 10%RH to 90%RH				
Operation Altitude	≥2000m @ full load and rated operating temperatures				
MTBF	≥50000Hrs @ full load and rated operating temperatures				
<b>Mechanical</b>					
Dimensions (W x L x H)	170.0 x 84.0 x 30.0mm (6.69 x 3.31 x 1.18 inch)				
Unit Weight	950g±25 grams				
Packing Information	15pcs/ Carton, carton dimensions:47*37*20cm, 15.0kgs/ Carton				

## TEST REPORT

### OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	RIPPLE & NOISE	300mVp-p (Max)	I/P:230VAC / O/P:FULL LOAD / Ta:25°C	219mVp-p	P
2	VOLTAGE TOLERANCE	-5% ~ +5% (Max)	I/P:90VAC~264VAC O/P:FULL~MIN. LOAD / Ta:25°C	-2% ~ +2% of output voltage	P
3	LINE REGULATION	-1% ~ +1% (Max)	I/P:90VAC ~264VAC O/P:FULL LOAD / Ta:25°C	-0.05% ~ +0.05% of output voltage	P
4	LOAD REGULATION	-3% ~ +3% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD / Ta:25°C	-1.45% ~ +1.45% of output voltage	P
5	SET UP TIME	3000 mS (Max)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	2200 mS	P
6	RISE TIME	100 mS (Max)	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	49 mS	P
7	HOLD UP TIME	8.3 mS (Min)	I/P: 115VAC O/P:FULL LOAD / Ta:25°C	13 mS	P

### INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	VOLTAGE RANGE	90VAC~264VAC	I/P:TESTING O/P:FULL LOAD / Ta:25°C	86V~264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 100VAC ~ 240VAC O/P:FULL~MIN LOAD / Ta:25°C	TEST: OK	P
3	EFFICIENCY	92% (Typ)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	93.5%	P
4	AVERAGE EFFICIENCY	>89% ( LEVEL VI)	I/P:115/230VAC & O/P:25%、50%、75%、100% LOAD & Ta:25°C	90.51% (115VAC) 90.76% (230VAC)	P
5	AC CURRENT	3.5A (Max)	I/P:100VAC & O/P:FULL LOAD Ta:25°C	3.28A	P
6	NO LOAD POWER CONSUMPTION	<0.21W	I/P: 230VAC /O/P:NO LOAD Ta:25°C	0.145W	P
7	INRUSH CURRENT	<140A COLD START	I/P: 230VAC / O/P:FULL LOAD Ta:25°C	68.16A	P
8	LEAKAGE CURRENT	< 0.25mA	I/P:240VAC & O/P:Min LOAD Ta:25°C	L-FG:0.18mA N-FG:0.14mA	P

### PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110 ~ 150% (Typ)	I/P:230VAC & O/P:TESTING Ta:25°C	119.23% HICCUP MODE	P
2	OVER VOLTAGE PROTECTION	CLAMP BY ZENER DIODE 115 ~ 135% (Typ)	I/P:230VAC O/P:MIN LOAD & Ta:25°C	CLAMP BY ZENER DIODE	P
3	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD & Ta:25°C	NO DAMAGE HICCUP MODE	P

### SAFETY TEST & E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3KVAC/min I/P- FG: 2KVAC/min O/P-FG:0.5KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 2.4 KVAC/min O/P-FG:0.6 KVAC/min Ta:25°C	I/P-O/P:2.189mA I/P-FG: 3.325mA O/P-FG:0.767mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 9999MΩ I/P-FG: 9999MΩ O/P-FG:9999 MΩ NO DAMAGE	P
3	CONDUCTION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL/50% LOAD Ta: 25°C	PASS Test by certified Lab	P
4	RADIATION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
5	SURGE	BS EN/EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P
6	E.S.D	BS EN/EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	LINDA	JUDY	ZHANG DL