



Features

- . Input voltage 110 /230VAC 50/60Hz or 200~360VDC
- . AC input range selectable by switch 110V or 230VAC
- . Output voltage select able from 5Vdc to 48Vdc for 320W series
- . Protections: Short Circuit / Overload / Over Voltage Protection
- . 100% full load burn-in test for 2Hrs to make every unit reliable
- . Forced air cooling by built-in DC ball bearing fan
- . Output voltage is adjustable by +/-10% of the rated output

Safety Standards

- . IEC62368-1 CB report for worldwide use
- . EN 62368-1:2014/A11:2017 for European Union
- . UL62368-1 + CAN/CSA 62368-1 for USA and Canada
- . AS/NZS 62368.1:2018 for Australia and New Zealand
- . J62368-1 for Japan and GB4943.1 for China market.



Product Description:

It is a low cost and high reliable 5Vdc 60A 300W single output constant voltage switching power supply solution with 110V / 230VAC input and the input range is selectable by switch. The product is designed and manufactured strictly according to the international safety standards. The output voltage is adjustable between 4.5V and 5.5V. The switching power supply utilizes aluminum alloy housing built-in a on/off controllable fan. This 5Vdc 60A power supply is suitable for various types of CCTV, EV Charging stations, Gate systems, Inspection systems, led screens display, new energy, railway, smart farming smart logistics, smart transportation and so on.

Technical Specification

Typ. Model	TL-320S-5	TL-320S-7.5	TL-320S-12	TL-320S-13.5	TL-320S-15
Output					
Output Voltage	5VDC	7.5VDC	12VDC	13.5VDC	15VDC
Rated Current	60A Max.	42.7A Max.	26.7A Max.	23.7A Max.	21.3A Max.
Current Range	0 ~ 60A	0 ~ 42.7A	0 ~ 26.7A	0 ~ 23.7A	0 ~ 21.3A
Output Power	300W Max.	320W Max.	320W Max.	320W Max.	320W Max.
Voltage Tolerance	±5%	±5%	±5%	±5%	±5%
Ripple & Noise	100mVp-p	100mVp-p	150mVp-p	150mVp-p	200mVp-p
Input					
Input voltage	110 / 230 Vac or 200- 360Vdc				
Input Frequency	50-60Hz (When the input is AC)				
Input Current	6.0 Max. @ 100 ~240Vac 50/60Hz input				
Inrush Current	60A Max. @ 100 ~240Vac 50/60Hz input				
Efficiency (Typ.)	79%	83%	86%	86%	86%
Leakage Current	≤0.5mA @ full input range				
Protections					
Over current	110~130% rated output power. Auto-Recovery when the fault is removed				
Short Circuit	No damage. Auto-Recovery when the fault is removed				
Over temperature	Shut down o/p voltage, re-power on to recover				
Environmental					
Operation Temperature	0°C to +45°C, 20%RH to 90%RH				
Storage Temp, Humidity	-45~ +85°C, 10%RH to 95%RH				
Operation Altitude	≤2000m @ full load and rated operating temperatures				
MTBF	≥50000Hrs @ full load and rated operating temperatures				
Mechanical					
Dimensions (W x L x H)	215.0 x 115.0 x 50.0mm (8.47 x 4.53 x 1.97 inch)				
Unit Weight	420g±20 grams				
Packing Information	28pcs/ Carton, carton dimensions:47*37*20cm, 12.5kgs/ Carton				

TEST REPORT

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	RIPPLE & NOISE	100mVp-p (Max)	I/P:230VAC / O/P:FULL LOAD / Ta:25°C	79mVp-p	P
2	VOLTAGE TOLERANCE	-5% ~ +5% (Max)	I/P:176VAC~264VAC O/P:FULL~MIN. LOAD / Ta:25°C	-2% ~ +2% of output voltage	P
3	LINE REGULATION	-1% ~ +1% (Max)	I/P:176VAC ~264VAC O/P:FULL LOAD / Ta:25°C	-0.11% ~ +0.12% of output voltage	P
4	LOAD REGULATION	-3% ~ +3% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD / Ta:25°C	-1.16% ~ +1.56% of output voltage	P
5	OVER/UNDERSHOOT	<±5%	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	0.98%	P
6	SET UP TIME	2000 mS (Max)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	1280 mS	P
7	RISE TIME	30 mS (Max)	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	28 mS	P
8	HOLD UP TIME	10 mS (Min)	I/P: 230VAC O/P:FULL LOAD / Ta:25°C	14 mS	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	VOLTAGE RANGE	90VAC~132VAC 176VAC~264VAC	I/P:TESTING O/P:FULL LOAD / Ta:25°C	85V ~ 132V 165V~264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 176VAC ~ 240VAC O/P:FULL~MIN LOAD / Ta:25°C	TEST: OK	P
3	EFFICIENCY	79% (Typ)	I/P:230VAC O/P:FULL LOAD / Ta:25°C	80.88%	P
4	AVERAGE EFFICIENCY	>77%	I/P:230VAC & O/P:25%、50%、75%、100% LOAD & Ta:25°C	78.58% (230VAC)	P
5	AC CURRENT	6.0A (Max)	I/P:230VAC & O/P:FULL LOAD Ta:25°C	2.93A	P
6	INRUSH CURRENT	<60A COLD START	I/P: 230VAC / O/P:FULL LOAD Ta:25°C	38.96A	P
7	LEAKAGE CURRENT	< 0.5mA	I/P:230VAC & O/P:Min LOAD Ta:25°C	L-FG:0.41mA N-FG:0.40mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110 ~ 130% (Typ)	I/P:230VAC & O/P:TESTING Ta:25°C	126.15% HICCUP MODE	P
2	OVER VOLTAGE PROTECTION	115 ~ 135% (Typ)	I/P:230VAC O/P:MIN LOAD & Ta:25°C	Hiccup mode, recovers automatically after fault condition is removed	P
3	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD & Ta:25°C	NO DAMAGE HICCUP MODE	P

SAFETY TEST & E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDIDTION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 1.5KVAC/min I/P- FG: 1.5KVAC/min O/P-FG:0.5KVAC/min	I/P-O/P: 1.8 KVAC/min I/P-FG: 1.8 KVAC/min O/P-FG:0.6 KVAC/min Ta:25°C	I/P-O/P:4.33mA I/P-FG: 4.33mA O/P-FG: 3.15mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 9999MΩ I/P-FG: 9999MΩ O/P-FG:9999 MΩ NO DAMAGE	P
3	CONDUCTION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL/50% LOAD Ta: 25°C	PASS Test by certified Lab	P
4	RADIATION	BS EN/EN55032(CISPR32), FCC PART 15 / CISPR22 CAN	I/P: 230 VAC (50HZ) O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
5	SURGE	BS EN/EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P
6	E.S.D	BS EN/EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA B	P

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	ZHU LI	WANG LW	ZHANG DL